

Test Report No. CANEC1407607501 Date: 29 May 2014 Page 1 of 18

AUSTIN HUGHES ELECTRONICS LTD.

UNIT 3608-12, CABLE TV TOWER 9 HOI SHING ROAD TSUEN WAN N T, HONG KONG

The following sample(s) was/were submitted and identified on behalf of the clients as: Powder Distribution Unit

SGS Job No. : CP14-026082 - GZ

Model No. : V4C13/2C19-30A-MT

Client Ref. Info. : SEE REMARK
Date of Sample Received : 20 May 2014

Testing Period : 20 May 2014 - 22 May 2014

Test Requested : Selected test(s) as requested by client.

Test Method: Please refer to next page(s).

Test Results: Please refer to next page(s).

Conclusion: Based on the performed tests on submitted samples, the results of Lead,

Mercury, Cadmium, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE) comply with the limits as set by RoHS

Directive 2011/65/EU Annex II; recasting 2002/95/EC.

Signed for and on behalf of SGS-CSTC Ltd.

SGS-CSTC Ltd.

Merry Lv

Approved Signatory



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflect the Company at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized atleration, foregery or falsification of the content or appearance of this document is unawful and offenders may be prosecuted to the fulles extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

198 Kezhu Road, Scientech Park Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075113 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075113 e sgs.china@sgs.com



Test Report

No. CANEC1407607501

Date: 29 May 2014

Page 8 of 18

REMARK:

Product Name: Power Distribution Unit

V & VP & H & HP difference:

V&VP is a Vertical type, denoted series coded identification. H&HP is a Horizontal type, denoted series coded identification.

First "X": denoted Outlet Number and Outlet Type, is Outlet Number may be 1 to 48, Outlet Type is may be "US" or "C13" or "C19" or "UK45" or "UK90" or "UK135" or "SCH" or "FR" or Other, "US" = NEMA, "C13" = IEC C13, "C19" = IEC C19, "UK45" = BS1363 45 degree, "UK90" = BS1363 90 degree, "UK135" = BS1363 135 degree, "SCH" = Schuko, "FR" = France, if multiple composition between Outlet type and Outlet Number is "/";

Second "X": denoted Total Output Ampere; is may be 0 to 99;

Third "X": denoted Control or Meter Type, is may be "MT" or "MTS" or "MD" or "W" or "WS" or "WS" or Blank, "MT" = Monitored PDU, "MTS" = Switched PDU, "MD" = Metered PDU, "W" = kWh Monitored PDU, "Wi" = Outlet Level kWh Monitored PDU, "WS" = kWh Switched PDU, "WSi" = Outlet Level kWh Switched PDU, Blank = Basic PDU;

Fourth "X": denoted Protect Type, is may be "F" or "CR" or "GF" or Other, "F" = Fuse, "CR" = Circuit Breaker, "GF" = Individual Fuse; Blank is not Protect;

Fifth X: denoted Input Plug and Wire Type, is may be "EN" or "C14" or "C20" or "OE" or "BS" or "CEE7" or "L620" or "L530" or "L530" or "520" or "530" or "515" or "TP" or Other, If there are two input Wires, followed by "/TP", "EN" = EN 60309, "C14" = C14 plug, "C20" = C20 plug, "OE" = Open End, "BS" = BS1363, "CEE7" = CEE7, "L620" = L6-20P, "L630" = L6-30P, "L520" = L5-20P, "L530" = L5-30P, "520" = 5-20P, "530" = 5-30P, "515" = 5-15P, "TP" = Twin Power Wire;



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without providing approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.



Test Report

No. CANEC1407607501

Date: 29 May 2014

Page 9 of 18

Sixth "X": denoted Cord Length, is may be "1" or "1.5" or "2" or "2.5" or "3" or "3.5" or "4" or "4.5" or "5" or Other, "1" = 1m / 3.28 feet;, "1.5" = 1.5m / 4.92 feet, "2" = 2m / 6.56Feet, "2.5" = 2.5m / 8.2 Feet, "3" = 3m / 9.84 Feet, "3.5" = 3.5m / 11.48 Feet, "4" = 4m / 13.1 Feet, "4.5" = 4.5m / 14.76 feet, "5" = 5m / 16.4 Feet;

Seventh "X": denoted place from, is may be "T" or "B" or Other, "T" = Top Feed, "B" = Bottom Feed is only for Vertical;

Eighth "X": denoted Outlet Case Color, is may be "1" or "2" or "3" or "4" or Other, "1" = Black, "2" = White, "3" = Red, "4" = Blue;

Ninth "X": denoted sensor type or filter type, is may be "T" or "TH" or "EMI" or "SPT" or other.

T = Temperature sensor; TH = Temperature & humidity sensor; EMI = EMI filter; SPT = Surge protector;;



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for Electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unafful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.